

4.5M C or Ku-Band Receive Only

Series 1451

Technical Specifications

Electrical	C-Band	Ku-Band
Antenna Size	4.5 M (15 ft.)	4.5 M (15 ft.)
Operating Frequency (GHz)	3.625 - 4.2 GHz	10.95 - 12.75 GHz
Midband Gain (+/- .5dB)	42.9 dBi	52.6 dBi
Polarization	Linear	Linear
3dB Beamwidth	1.2°	0.42°
Feed Interface	CPR 229	WR 75
Cross-Pol Isolation (Linear)	>30 dB Min. (on axis)	>30 dB Min. (on axis)
First Sidelobe (typical)	- 20 dB	- 20 dB
VSWR	1.3:1 Max.	1.3:1 Max.

Mechanical	
Reflector Material	Glass Fiber Reinforced Polyester SMC
Antenna Optics	8 Piece Axisymmetric, Prime Focus
Mast Pipe Size	10" SCH 40 Pipe (10.75" OD) 27.30 cm.
Elevation Adjustment Range	5° to 90° Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous
Shipping Specifications (Weight)	950 lbs. (428 kg.)

Environmental Performance	
Wind Loading Operational Survival	45 mph (72 km/h) 125 mph (201 km/h)
Temperature Operational Survival	-40° to 140° F (-40° to 60° C) -50° to 160° F (-46° to 71° C)
Atmospheric Conditions	Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Solar Radiation	360 BTU/h/ft2

BUY NOW

GENERAL DYNAMICS
SATCOM Technologies

1000-002 Rev. 05/11